


Seamless Design

Every Panel is manufactured with CNC auto-machines of high precision so that to guarantee its seamlessness during assembly.



- Support for both front and rear maintenance.
- Uniform color and high contrast ensure clear and sharp picture .
- High precision die-casting aluminum panel achieves high flatness and seamless matching of the whole display.
- Fan-less design with good dissipation guarantees noise-free effect.
- Light and slim panel is easy to handle and transport.
- High stability and reliability prolong the lifespan of LED display.

SPECS

Item	Value	Value	Value	Value
Pixel Pitch(mm)	2.5	3	3.9	4
Pixel Density(pixels/m ²)	160000	111111	65536	62500
Viewing Angle(Deg.)	H: 160/ V: 160	H: 160/ V: 160	H: 160/ V: 160	H: 160/ V: 160
Brightness(nits)	1200	1500	1500	1500
Grey Level(bit)	12/14/16	12/14/16	12/14/16	12/14/16
Refresh Rate(Hz)	1920/2880/3840	1920/2880/3840	1920/2880/3840	1920/2880/3840
Panel Dimension(mm)	64(W)x64(H)	576(W)x576(H)	500(W)x500(H)	512(W)x512(H)
Panel Dimension(inch)	25.19(W)x25.19(H)	22.68(W)x22.68(H)	19.68(W)x19.68(H)	20.15(W)x20.15(H)
Panel Resolution(pixels)	256x256	192x192	128x128	128x128
Panel Type and Material	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum
Panel Weight(kg)	15	11	11	11
Module Size(mm)	160(W)x160(H)	192(W)x192(H)	250(W)x250(H)	256(W)x128(H)
Module Size(inch)	6.29(W)x6.29(H)	7.55(W)x7.55(H)	9.84(W)x9.84(H)	10.07(W)x5.03(H)
Protection Grade	IP30	IP30	IP30	IP30
Serviceability	Rear	Rear	Rear	Rear
Avg.Power Consumption(W/m ²)	143(AC)	143(AC)	143(AC)	143(AC)
Max.Power Consumption(W/m ²)	570(AC)	570(AC)	570(AC)	570(AC)
Brightness Adjustment	Manual/Auto/Programmable	Manual/Auto/Programmable	Manual/Auto/Programmable	Manual/Auto/Programmable
Operating Temp/Humidity(°C/%RH)	-20~+50/10~90	-20~+50/10~90	-20~+50/10~90	-20~+50/10~90
Storage Temp/Humidity(°C/%RH)	-40~+60/0~90	-40~+60/0~90	-40~+60/0~90	-40~+60/0~90
Lifetime(hours)	100000(Nomal Temp)	100000(Nomal Temp)	100000(Nomal Temp)	100000(Nomal Temp)
Compliant Standard	CE,FCC,RoHS	CE,FCC,RoHS	CE,FCC,RoHS	CE,FCC,RoHS

Notes: Specifications are for reference only. Please contact our Sales Manager for details. All rights are reserved to Company LED World sarl.